

351026 Wireless 2D Barcode Scanner, Long Distance, with Stand

Product Images



Features



Product Diagram





Short Description

- Wireless 2D CMOS IMAGE Barcode Scanner
- With frequency 433MHz ISM Band
- Communication range : 100-200 meters in open area
- Precise scanning of 1D & 2D barcodes, (barcodes & QR code)
- Efficiently deciphers linear barcodes for retail and inventory management.
- Wireless Connectivity: with frequency 433MHz ISM Band
- Durable Construction: Robust design to withstand daily use and potential drops.
- Protected and water-resistant (IP54)
- Wide Scan Range: Reads barcodes from various distances and angles.
- Multiple Scanning Modes: Options for manual, continuous , Auto-induction mode scanning.
- Plug-and-play functionality for quick setup
- Pairing ability base station support up to 20 scanners connection
- Memory save over 2,000 scans data (@ barcode length < 15 bytes)
- Power Source USB from PC / Host system. charging station included.
- Build in battery 3.7V 1500mAh Li-ion.
- Working time : around 20hours, Standby: 3 months.
- **Please charging Barcode Scanner battery before using.

Description

The Equip Wireless 2D Barcode Scanner with Long-Distance Capability and Stand is a versatile and efficient scanning solution for various industries. This device allows you to effortlessly capture 2D barcodes from a distance, making it ideal for retail, warehousing, and inventory management applications. With the included stand, it can be used hands-free, enhancing productivity and reducing user fatigue. This scanner offers exceptional performance and connectivity options, ensuring seamless integration into your existing systems. Its wireless capabilities provide flexibility, while its long-distance scanning capability ensures reliable data capture, even from a distance. Whether you need to scan barcodes on products, shelves, or packages, this scanner simplifies the process, streamlining operations and improving accuracy.

Additional Information

Color	Black
EAN	4015867234297
Model Number	351026
Decoding Type 1D	Code 128、EAN-13、EAN-8、Code 39、UPC-A、UPC-E、Codabar、Interleaved 2 of 5、Industrial 2 of 5、Standard 2 of 5、Matrix 2 of 5、ISBN/ISSN、Code 93、codeUCC/EAN-128、GS1 Databar、Code39、Code11、MSI-Plessey、Plessey
Decoding Type 2D	PDF417、QR Code、Data Matrix
Depth of Field	EAN13 (13mil) 35mm~210mm PDF417 (6.67mil) 30mm~180mm QR Code (screen) 50mm~600mm QR Code (15mil) 30mm~350mm
Light Source (color)	WHITE LED
Protection	IP54
Scan Angle	Roll : 360°, Pitch : ±30°, Skew : ±35°
Scan Distance	1500mm
Scan Speed	220 Scans / per sec
Trigger Mode	Manual, Continuous Scan, Auto-induction Scan
Connection mode	WIFI (433MHz ISM Band)
Approval and Compliance	CE, RoHS
Operating humidity	5% RH ~ 95% RH
Operating temperature	-20°C ~ 60°C
Compatible operating systems	WIN XP/7/8/9/10 Android IOS LINUX
Storage temperature	-40°C ~ 85°C
Package Contents	Barcode Scanner Quick Installation Guide Charging Receiver Stand
Cable length	1.8M
Dimensions (W x D x H)	111 x 175 x 180 mm
Product weight (kg)	0.445

Wireless connection	Yes
Battery capacity (mAh)	1500
Battery capacity (Wh)	5.55
Battery type	Lithium Ion
Battery voltage	3.7
Material	ABS
Power supply	USB
Resolution	≥ 4mil for 1D ≥ 5mil for 2D

